

Add color images, graphics, and variable data to envelopes and documents for more effective communication with the new HP Color Print Module—a modular print solution that easily and cost-effectively integrates into your existing equipment.





## Excellent color print quality at high speeds

Increase promotional effectiveness and response rates with high-speed, high-quality variable color added to envelopes and Web printed pages. Produce color images, graphics, and variable data 600 dpi (600x300 dpi optimized from 300x300 input) at 400 fpm with four 4.25" printheads.

- See high-quality color output that is delivered quickly
- Self-servicing printheads from HP optimize color quality and enable consistent, reliable operation
- Achieve quality color and save time with HP inks and two self-switching 775-ml ink containers for each color



Offering a low total cost of ownership, the HP Color Print Module is an affordable option for adding process color, especially versus standalone equipment. Plus you save time and money with automatic maintenance and low processing costs.



The HP Color Print Module has a modular design to easily integrate with your existing equipment and workflow.

- Easy to integrate with your existing analog or finishing equipment
- Flexible implementation—integrate the HP Color Print Module where it's most convenient for your workflow







## **TECHNICAL SPECIFICATIONS**

GENERAL DESCRIPTION	TIJ 4 print system for process color variable data printing with four easily replaceable printheads including:
	Intelligent Print Driver (IPD)
	Intelligent Ink Supply Station (I2S2)
	Intelligent Service Station (ISVS)
	Back-end data pipeline (IPIPE)
NOZZLES	4 x 5 die TIJ 4 printheads (one per color)
	2 columns per printhead @ 5,280 nozzles each
	10,560 nozzles total per printhead
	42,240 total nozzles per print module
PRINT SWATH	108 mm (4.25")
RESOLUTION	600 dpi (600x300 dpi optimized from 300x300 input)
DROP SIZE	6-9 ng/drop (depending on ink type)
PRINT SPEED	Up to 2 m/sec (400 fpm)
TIME BETWEEN PAGES	50 ms minimum
IMAGE PROCESSING TIME	22 ms/Mpixel @ 300x300 input resolution
INK TYPES AVAILABLE	Dye-based
ink colors	Cyan 6 ng drop Magenta 6 ng drop Yellow 6 ng drop Black 9 ng drop
BULK INK SUPPLIES	2 hot-swappable 775 ml ink supplies per color
COLOR CAPABILITIES	CMYK process color
PRINTHEAD IDENTIFICATION	Smart chip
PRINTHEAD SERVICING	Automated servicing (wiping, capping, spitting) Servicing requirements: ~30 seconds each hour
PEN TO PAPER SPACING	1.2 - 2.0 mm for optimum print quality
PRINTHEAD ORIENTATION	Printing vertically downward
PRINTHEAD REPLACEMENT TIME	<5 MIN
PRINTHEAD SHELF LIFE	18 months in original packaging
PRINTHEAD LIFE	~30 liters/printhead
OPTIMUM OPERATING ENVIRONMENT	15-35 °C, 20-80% RH
IMAGER DIMENSIONS	483 mm (19")H x 432 mm (17")D x 508 mm (20")W

This is a preliminary datasheet and contents may be subject to change.

For more information visit: http://www.hp.com/go/oeminkjet

© 2010 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.